



# 20x10ft



## Frame Specifications

### Frame Construction

**Frame Material**  
**Leg Shape & Profile**  
**Truss Profile**  
**Connecting Elements**  
**Push-Button Locks**  
**Corner Brackets**

	S1 	S2 
<b>Weight</b>	123.6lbs. (56.2kg)	102.5lbs. (46.6kg)
<b>Transport Bag</b>	Heavy-Duty PVC with Window	Heavy-Duty PVC with Window

3x Strong, All-Aluminum (T606)  
 Octagonal Leg, 43mm (2.5mm)  
 30x15mm (2.8mm)  
 ✓ Aluminum with Rubber Caps  
 ✓ Comfort Press  
 ✓ Spring Tension & Corner Clips

2x Strong, All-Aluminum (T606)  
 Octagonal Leg, 37mm (2.1mm)  
 28.5x15mm (2mm)  
 ✓ Aluminum with Rubber Caps  
 ✓ Comfort Press  
 ✓ Fixed Position & Corner Clips

## Customization Options

### Roof Styles



### Frame Colors



### Frame Height Extensions

✓ Up to 36"

✓ Up to 12"

### Peak Flag & Banner Capable

✓ Frame & Roof Integrated

✓ Frame & Roof Integrated

Our professional-grade tents can mix and match frame and fabric quality, roof styles, colors, customizations, and more.

**Rely on your Product Expert or visit our quick links:**

[Mastertent Website](#)

[3D Tent Configurator](#)

[Tent Sizes](#)

[Photo Gallery](#)

[Construction Details](#)

[Warranties & Certificates](#)



### Custom Printing

Individual Logo or Full Surface 

### Roof Fabric Options

Pirontex®, Oxford Weave 500D Polyester, Heavy-Duty PVC, Fiberglass, Loden

### Textile Properties

**Waterproof Rating**  
(DIN EN 20811)

### Pirontex®

✓ 5x Industry Avg  
5,000mm Water Column

### Oxford 500D

✓ 2x Industry Avg  
1,600mm Water Column

### Fire Rating Class

B - s2, d0 (difficult to ignite)

NFPA 701, CPAI-84 Sec.6, EN 13501-1:2019, CAN/ULC-S109, CA Title 19 Sec. 1237

### Color Fade Resistance

(DIN EN ISO 105-B02)

Extreme

(blue scale 7.0-8.0 of 8.0)

Durable

(blue scale 4.5-6.5 of 8.0)