


26x13ft Awning Tent Models



Frame Specifications


S1



Frame Construction

Frame Material	3x Strong, All-Aluminum (T606)
Leg Shape & Profile	Octagonal Leg, 43mm (2.5mm)
Truss Profile	30x15mm (2.8mm)
Connecting Elements	✓ Aluminum with Rubber Caps
Push-Button Locks	✓ Comfort Press
Corner Brackets	✓ Spring Tension & Corner Clips
Transport Bag	Heavy-Duty PVC with Window

Awning Model	Weight	Entrance Height	Peak Height	Awning Depth	Pack Size (L x W x H)
1-Awning	82.7lbs (37.6kg)	6' 8" (202cm)	11' 7" (353cm)	31.4" (80cm)	17.3 x 16.5 x 62"
2-Awning	86.5lbs (39.3kg)	6' 8" (202cm)	11' 7" (353cm)	31.4" (80cm)	20.8 x 20.2 x 66"
3-Awning	95.3lbs (43.3kg)	6' 8" (202cm)	11' 7" (353cm)	31.4" (80cm)	20.8 x 20.2 x 66"
4-Awning	87.3lbs (39.7kg)	6' 8" (202cm)	13' 6" (412.5cm)	31.4" (80cm)	20.8 x 20.2 x 66"



Custom Printing
Individual Logo or Full Surface

Roof Fabric Options
Pirontex®, Oxford Weave 500D
Polyester, Heavy-Duty PVC, Fiberglass, Loden

Customization Options

Frame Colors



200+ Custom RAL Colors

Frame Height Extensions

✓ Up to 36"

Peak Flag Capable

✓ Frame & Roof Integrated

Textile Properties	Pirontex®	Oxford 500D
Waterproof Rating (DIN EN 20811)	✓ 5x Industry Avg 5,000mm Water Column	✓ 2x Industry Avg 1,600mm Water Column
Fire Rating Class B - s2, d0 (difficult to ignite)	NFPA 701, CPAI-84 Sec.6, EN 13501-1:2019, CAN/ULC-S109, CA Title 19 Sec. 1237	
Color Fade Resistance (DIN EN ISO 105-B02)	Extreme (blue scale 7.0-8.0 of 8.0)	Durable (blue scale 4.5-6.5 of 8.0)